

# VYBO Electric a.s.



## Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer

Client reference

Type

4AL-80M 2-2 1,1KW 230/400V 50HZ

Brand

VYBO Electric

### Identification

Type:	4AL-80M 2-2		Frame:	80		mm
Power:	1,1	kW	Poles:	2		P
Rated Current:	380 V	2,4	Rated Voltage:	230	/	400 V
	400 V	2,2		Connection: Δ/Y		
	415 V	2,2		Insulation Class: F		
Speed:	2920	rpm	Temperature Rise:			
Frequency:	50	Hz	Service Factor:	1,0		
Direct on line starting torque ratio (LRT/RLT):	2,2		Duty:	S1, S2, S3, S4-S9		
Direct on line pull out torque ratio (BDT/RLT):	2,3		Ambient Temperature:	-35~50°C		
Direct on line starting current ratio (LRA/RLA):	8,5		Altitude:	1000m		
Efficiency:	85,2	%	Protection Degree:	IP55		
Power factor:	0,83		Cooling:	IC411		
Noise level:	62	dB(A)	Mounting:	IM B (On request)		
Weight:	25	kg	Vibration:	2.8 mm/s		
Rotor inertia:	0,00145	kg/m2	Direction of Rotation:	Both		
			Starting Method:	DOL or VFD		
			Coupling:	DIRECT		
			Load Type:	Parabolic or linear curve		
			Terminal box:	2-M20X1.5		



### Bearing Information

	DE	NDE
Bearing:	62042RZ	62042RZ
Regreasing int.(h):		
Grease amount(g):		
Grease:		

### Notes / Accessories

### Deviation Sheet

Notes / Accessories		Deviation Sheet	
		VYBO Electric	Customer

### Standards

Specification:	IEC60034-1 / GB755	
Test:	IEC60034-2 / GB/T1032	
Noise:	IEC60034-9 / GB10069.3	
Vibration:	IEC60034-14 / GB10068	

### Edition

Performed	Checked	Date



Item	Changes	Performed	Checked	Date