

VYBO Electric a.s.								
Data Sheet			No.					
Three Phase Induction Motor			Drawing No.					
Customer								
Client reference								
Type				4AL-132S 2-2 7,5KW 400/690V 50HZ				
Brand				VYBO Electric				
Identification								
Type:	4AL-132S 2-2			Frame:	132		mm	
Power:	7,5 kW			Poles:	2		P	
Rated Current:	380 V	14,1	A	Rated Voltage:	400	/	690 V	
	400 V	13,4		Connection:	Δ/Y			
	415 V	12,9		Insulation Class:	F			
Speed:	2950 rpm			Temperature Rise:				
Frequency:	50 Hz			Service Factor:	1,0			
Direct on line starting torque ratio (LRT/RLT):	2			Duty:	S1, S2, S3, S4-S9			
Direct on line pull out torque ratio (BDT/RLT):	2,3			Ambient Temperature:	-35~50°C			
Direct on line starting current ratio (LRA/RLA):	9,5			Altitude:	1000m			
Efficiency:	91,7	%		Protection Degree:	IP55			
Power factor:	0,89			Cooling:	IC411			
Noise level:	79	dB(A)		Mounting:	IM B (On request)			
Weight:	81	kg		Vibration:	2.8 mm/s			
Rotor inertia:	0,01675	kg/m2		Direction of Rotation:	Both			
				Starting Method:	DOL or VFD			
				Coupling:	DIRECT			
				Load Type:	Parabolic or linear curve			
				Terminal box:	2-M32X1.5			
				Bearing Information				
					DE		NDE	
				Bearing:	63082RZ		63082RZ	
				Regreasing int.(h):				
				Grease amount(g):				
Grease:								
Notes / Accessories				Deviation Sheet				
				VYBO Electric		Customer		
Standards								
Specification:	IEC60034-1 / GB755							
Test:	IEC60034-2 / GB/T1032							
Noise:	IEC60034-9 / GB10069.3							
Vibration:	IEC60034-14 / GB10068							
Edition								
Performed		Checked		Date				
Item	Changes			Performed	Checked	Date		